



Nuova Ricambi srl

Version no. 2

Revision date 27/07/2015

CLEAN EXPRESS LIQUIDO

Printed on 27/07/2015

Page no. 1/16

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and the company/undertaking

1.1. Product identification

Name **CLEAN EXPRESS LIQUIDO**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description/Use **Liquid detergent for coffee machine cleaning**

1.3. Details of the supplier of the safety data sheet

Company name **Nuova Ricambi srl**
Address **Via Dei Mille, 20**
City and Country **20061 Carugate (MI)**
Italy
tel. 02 9253205
fax 02 92157705

e-mail of the competent person,
person responsible for the safety data
sheet **info@nuovaricambi.it**

1.4. Emergency telephone number

For urgent information contact **Poison Center: 02/66101029- Company headquarters: tel 02/9253205**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions of Regulation (EC) 1272/2008 (CLP) (and amendments). Therefore the product requires a safety data sheet according to the provisions of Regulation (EC) 1907/2006 and subsequent amendments.

Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Classification and hazard statements:

Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.

2.2. Labeling elements.

Danger identification pursuant to Regulation (EC) 1272/2008 (CLP) and subsequent amendments.



Warnings: **Hazard**

**CLEAN EXPRESS LIQUIDO**

Hazard statements:

H314 Causes severe skin burns and eye damage.

Precautionary statements:

P264 Wash thoroughly with water after handling.
P280 Wear protective gloves/protective clothing and eye protection/face protection.
P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.
P310 Immediately call a POISON CENTER/doctor / . . .

Contains: POTASSIUM HYDROXIDE
ALCHYLPOLYGLUCOSIDE C8-C10
SODIUM METASILICATE PENTAHYDRATE

2.3. Other hazards.

According to the available data, the product does not contain PBT or vPvB substances in a percentage higher than 0.1%.

SECTION 3. Ingredients/composition information.**3.1. Substances.**

Information non applicable.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
POTASSIUM HYDROXIDE CAS. 1310-58-3 EC. 215-181-3 INDEX. 019-002-00-8 Nr. Reg. 01-2119487136-33	5 - 10	Met. Corr. 1 H290, Acute Tox. 4 H302, Skin Corr. 1A H314
2-(2-BUTOXYETHOXY)ETHANOL CAS. 112-34-5 EC. 203-961-6 INDEX. - Nr. Reg. 01-2119475104-44	5 - 10	Eye Irrit. 2 H319
ALCHYLPOLYGLUCOSIDE C8-C10 CAS. 68515-73-1 EC. 500-220-1 INDEX. - Nr. Reg. 01-2119488530-36	0 - 5	Eye Dam. 1 H318
SODIUM METASILICATE PENTAHYDRATE CAS. 10213-79-3	0 - 5	Met. Corr. 1 H290, Skin



Nuova Ricambi srl

Version no. 2

Revision date 27/07/2015

CLEAN EXPRESS LIQUIDO

Printed on 27/07/2015

Page no. 3/16

Corr. 1B H314, STOT
SE 3 H335

EC. 229-912-9

INDEX. -

Nr. Reg. 01-2119449811-37-xxx

Note: Upper range value excluded.

The full text of the hazard statements (H) is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if worn. Immediately flush eyes with plenty of water for at least 30/60 minutes while keeping eyelids raised. Seek medical advice immediately.

SKIN: Remove any contaminated clothing. Shower immediately. Seek medical advice immediately.

INGESTION: Make the person drink as much water as possible. Seek medical advice immediately. Do not induce vomiting unless expressly authorized to do so by the doctor.

INHALATION: Call a doctor immediately. Remove the person to fresh air, away from the place of the accident. If the person stops breathing, perform artificial respiration. Take suitable precautions for the first-aider.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures

5.1. Extinguishing media.

APPROPRIATE EXTINGUISHING MEDIA

Use conventional extinction equipment: carbon dioxide, foam, powder and nebulized water.

INAPPROPRIATE EXTINGUISHING MEDIA

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Avoid inhaling any combustion products.

5.3. Advice for firefighters.



Nuova Ricambi srl

Version no. 2

Revision date 27/07/2015

Printed on 27/07/2015

Page no. 4/16

CLEAN EXPRESS LIQUIDO

GENERAL INFORMATION

Cool the containers with jets of water to prevent product decomposition and the development of substances that are potentially hazardous for the health. Always wear full fire protection equipment. Collect all water used to extinguish the fire; this must not be drained into the mains sewer. Dispose of contaminated water used to extinguish the fire and other fire residues in compliance with the laws in force.

EQUIPMENT

Normal firefighting clothing, such as self-contained, open-circuit compressed air breathing apparatus (EN 137), flameproof suit (EN469), flameproof gloves (EN 659) and Fire Brigade boots (HO A29 or A30).

Penta Sodium Metasilicate: use respiratory protection.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear appropriate protection devices (including personal protective equipment as listed in section 8 of the safety data sheet) to prevent contamination of skin, eyes and personal clothing. These indications are valid for both workers during handling and emergency interventions.

6.2. Environmental precautions

Do not allow the product to penetrate into sewers, surface and ground waters.

6.3. Methods and material for containment and cleaning up

Aspirate the leaked product into appropriate containers. Assess the compatibility of the container to use with the product, checking section 10. Absorb the remaining product with inert absorbent materials.

Make sure that the leakage site is well aired. Check any incompatibility of the materials with the containers in section 7. Contaminated material must be disposed of in compliance with the provisions laid down in point 13.

6.4. Reference to other sections

Any information concerning personal protection and disposal are given in sections 8 and 13.

SECTION 7. Handling and storage

DO NOT store in containers other than the original one; risk of fatal errors if exchanged for drinks.

7.1. Precautions for safety handling

Ensure appropriate earthing for the systems and persons. Avoid contact with eyes and skin. Do not inhale any dust, vapors or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid release to the environment.

Penta Sodium Metasilicate: avoid inhaling powders.



CLEAN EXPRESS LIQUIDO

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well-ventilated place away from sources of ignition. Keep the containers hermetically sealed. Store the product in clearly labeled containers. Avoid overheating. Avoid violent knocks. Keep the containers away from any incompatible materials, check section 10.

Store at a temperature of no more than 40 °C.

7.3. Specific end use(s)

Information not available.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Reference Regulations:

CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail 2012. / Grenzwerte am Arbeitsplatz
ITA	Italy	Legislative Decree no. 81 of 9 April 2008
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	State	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
VEL	CHE	67	10	101.2	15
MAK	CHE	67	10	101.2	15
TLV	ITA	67.5	10	101.2	15
OEL	EU	67.5	10	101.2	15
TLV-ACGIH		66	10		

Predicted no effect concentration in the environment - PNEC.

Reference value for STP micro-organisms 200 mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of Exposure	Effects on consumers				Effects on workers			
	Local acute	Systemic acute	Local chronic	Systemic chronic	Local acute	Systemic acute	Local chronic	Systemic chronic
Inhalation.							67.5 mg/m ³	67.5 mg/m ³

POTASSIUM HYDROXIDE

Threshold Limit Value

Type	State	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm



CLEAN EXPRESS LIQUIDO

TLV-ACGIH

2 (C)

Health - Derived no-effect level - DNEL / DMEL

Route of Exposure	Effects on consumers				Effects on workers			
	Local acute	Systemic acute	Local chronic	Systemic chronic	Local acute	Systemic acute	Local chronic	Systemic chronic
Inhalation.							1 mg/m3	VND

ALCHILPOLIGLUCOSIDE C8-C10

Predicted no effect concentration in the environment - PNEC.

Reference value for STP micro-organisms 560 mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of Exposure	Effects on consumers				Effects on workers			
	Local acute	Systemic acute	Local chronic	Systemic chronic	Local acute	Systemic acute	Local chronic	Systemic chronic
Inhalation.							VND	420 mg/m3

Key:

(C) = CEILING ; INHALAB = Inhalable Fraction ; RESPIR = Respirable Fraction ; TORAC = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NHI = no hazard identified.

8.2. Exposure controls

Considering that the use of appropriate technical measures should always take priority over personal protective equipment, ensure that the working environment is well ventilated using a local aspiration system. Personal protective equipment must carry the CE marking to certify conformity to the regulations in force.

Provide emergency eye wash and shower facilities.

HAND PROTECTION

Protect the hands with category III work gloves (ref. EN 374).

In choosing appropriate work glove material consider: compatibility, degradation, breakage time and permeation.

Work glove resistance to chemical agents for preparations must be checked before use, as it could be unpredictable.

Glove wear depends on the duration and methods of use.

SKIN PROTECTION

Wear category III professional work clothes with long sleeves and safety footwear (ref. Directive 89/686/EEC and standard EN ISO 20344). Wash with soap and water after removing protective clothing.

EYE PROTECTION

It is recommended to wear a protective hood or visor combined with airtight goggles (ref. standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) of the substance or one or more of the substances in the product is exceeded, wear a mask with an A type filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use. (ref. EN 14387). In the presence of gas or other types of vapors and/or gas or vapors with particles (aerosol, fumes, mist, etc.)



CLEAN EXPRESS LIQUIDO

use combined filters.

Respiratory protection must be used if the technical measures adopted are not sufficient to limit the exposure of the workers to the considered threshold values. The protection provided by masks is in any case limited.

If the substance in question is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear self-contained, open-circuit compressed air breathing apparatus (ref. EN 137) or fresh air hose breathing apparatus (ref. EN 138). Refer to standard EN 529 to choose the appropriate respiratory protection.

ENVIRONMENTAL EXPOSURE CONTROLS

Production process emissions, including those from ventilation equipment, must be checked in order to comply with environmental protection regulations.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Brown
Odor	Characteristic
Olfactory threshold.	Not available.
pH.	11.92 (sol. 1%)
Melting or freezing point	Not available.
Initial boiling point	Not available.
Boiling interval	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability of solids and gases	Not available.
Lower flammability limit	Not available.
Upper flammability limit	Not available.
Lower explosive limit	Not available.
Upper explosive limit	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.080 Kg/l
Solubility	Soluble in water
Partition coefficient: n-octanol/water	Not available.
Ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidizing properties	Not available.

9.2. Other information

VOC (Directive 1999/13/EC):	0
VOC (volatile carbon):	0

SECTION 10. Stability and reactivity

10.1. Reactivity

**CLEAN EXPRESS LIQUIDO**

There are no particular risks of reaction with other substances in normal conditions of use.

POTASSIUM HYDROXIDE: potential isothermal hazard. May be corrosive to metals.

SODIUM METASILICATE PENTAHYDRATE: aqueous solutions behave like strong alkalis; they may corrode aluminium, zinc, tin and relative alloys.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

POTASSIUM HYDROXIDE: stable in the recommended storage conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

POTASSIUM HYDROXIDE: frees hydrogen when reacting with metals. Isothermal reaction with strong acids. Reacts violently with water.

SODIUM METASILICATE PENTAHYDRATE: reacts violently with acids.

2-(2-BUTOXYETHOXY)ETHANOL: may react with oxidants. May form peroxides with atmospheric oxygen. May produce hydrogen when reacting with aluminium. May form explosive mixtures with air.

10.4. Conditions to avoid

None in particular. However take all the usual precautions adopted when handling chemicals.

POTASSIUM HYDROXIDE: Instable when exposed to the air. Freezing.

2-(2-BUTOXYETHOXY)ETHANOL: avoid contact with the air.

10.5. Incompatible materials

POTASSIUM HYDROXIDE: keep separate from: heat sources, oxidizing agents, acids, highly flammable materials, halogens, organic materials. Keep away from: lead, aluminum, copper, tin, zinc, bronze.

2-(2-BUTOXYETHOXY)ETHANOL: oxidizing substances, strong acids and alkaline metals.

10.6. Hazardous decomposition products

POTASSIUM HYDROXIDE: absorbs atmospheric CO₂. Hydrogen: Reacts with (some) metals and their compounds; releases highly flammable gas.

2-(2-BUTOXYETHOXY)ETHANOL: hydrogen.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

If no experimental toxicological data is available for the product, any health hazards have been assessed according to the

**CLEAN EXPRESS LIQUIDO**

properties of the contained substances, in line with the criteria laid down in the reference regulations for the classification. Therefore consider the concentration of any single hazardous substances referred to in sect. 3, to assess the toxicological effects deriving from exposure to the product.

The product is corrosive and causes serious skin burns and blisters which may also appear after exposure. The burns can cause stinging and pain. On contact with eyes it causes severe lesions and can cause corneal opacity, damage to the iris, irreversible colouring of the eye. Any vapors and/or dust are caustic for the respiratory tract and can cause lung oedema, the symptoms of which may sometime appear only after several hours. Symptoms of exposure may include: a burning sensation, coughing, asthmatic breathing, laringitis, shortage of breath, nausea and vomiting. Ingestion can seriously burn the mouth, throat and esophagus; it may cause vomiting, diarrhoea, oedema, swelling to the larynx and consequent suffocation. Severe cases may include the perforation of the gastrointestinal tract.

The product causes severe lesions and can cause corneal opacity, damage to the iris, irreversible colouring of the eye.

2-(2-BUTOXYETHOXY)ETHANOL: can be absorbed by inhalation, ingestion and skin contact; it is an irritant for the skin and particularly for the eyes. It may also cause damage to the spleen. At room temperature danger from inhalation is improbable, due to the low vapour pressure of the substance.

ALCHILPOLIGLUCOSIDE C8-C10

LD50 (Oral).> 5000 mg/kg oral rat

POTASSIUM HYDROXIDE

LD50 (Oral).333 mg/kg Rat

SODIUM METASILICATE PENTAHYDRATE

LD50 (Oral).> 1150 mg/kg Rat

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Oral).3384 mg/kg Rat

LD50 (Skin).2700 mg/kg Rabbit

SECTION 12. Ecological information

Use this product according to good working practices; do not litter. Inform the competent authorities if the product reaches waterways or sewers or if it contaminates soil or vegetation.

12.1. Toxicity**ALCHILPOLIGLUCOSI**

DE C8-C10

LC50 - Fish. > 100 mg/l/96h

POTASSIUM

HYDROXIDE

LC50 - Fish. > 80 mg/l/96h

SODIUM

METASILICATE

PENTAHYDRATE

LC50 - Fish. > 210 mg/l/96h Brachydanio R.

2-(2-

BUTOXYETHOXY)ETH

**CLEAN EXPRESS LIQUIDO**

ANOL
LC50 - Fish. > 1300 mg/l/96h Lepomis M.

12.2. Persistence and degradability

POTASSIUM
HYDROXIDE
Solubility in water. > 10000 mg/l
Biodegradability: Figures not Available.

2-(2-
BUTOXYETHOXY)ETH
ANOL
Solubility in water. mg/l 1000 - 10000
Rapidly Biodegradable.

The product contains substances conforming to the provisions of Reg 648/04/EC.

12.3. Bioaccumulative potential

2-(2-
BUTOXYETHOXY)ETH
ANOL
Partition coefficient: n- 1
octanol/water.

12.4. Mobility in the soil

Information not available.

12.5. Results of PBT and vPvB assessment

According to the available data, the product does not contain PBT or vPvB substances in a percentage higher than 0.1%.

12.6. Other adverse effects

Information not available.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, if possible. Product residues are considered special hazardous waste. The hazard level of the waste which partially contains this product must be assessed according to the legal provisions in force.

The product must be disposed of by an authorized waste management company, in compliance with the national and any local laws.

Waste transport may be subject to the ADR.



Nuova Ricambi srl

Version no. 2

Revision date 27/07/2015

CLEAN EXPRESS LIQUIDO

Printed on 27/07/2015

Page no. 11/16

CONTAMINATED PACKAGING

Contaminated packaging must be sent for recycling or disposal in compliance with the national waste management laws.

SECTION 14. Transport information

For cartons of 20 x 1 l bottles ADR 3.4. applies

14.1. UN number.

ADR / RID, 1719
IMDG, IATA:

14.2. UN shipping number.

ADR / RID: CAUSTIC
ALKALI
LIQUID,
N.A.S.
(Potassium
hydroxide)
IMDG: CAUSTIC
ALKALI
LIQUID,
N.O.S.
IATA: CAUSTIC
ALKALI
LIQUID,
N.O.S.

14.3. Transport hazard classes.

ADR / RID: Class: 8 Label: 8
IMDG: Class: 8 Label: 8
IATA: Class: 8 Label: 8



14.4. Packing group.

ADR / RID, II
IMDG, IATA:

14.5. Environmental hazards.

ADR / RID: NO

14.6. Special precautions for users.

ADR / RID: HIN - Kemler: - Limited Quantity 1 Tunnel restriction



Nuova Ricambi srl

Version no. 2

Revision date 27/07/2015

Printed on 27/07/2015

Page no. 12/16

CLEAN EXPRESS LIQUIDO

IMDG:	Special provisions: 274 EMS: F-A, S-B	I	code E
IATA:	Cargo:	Limited Quantity 1	
	Pass.:	I	
	Special instructions:	Maximum quantity: -	Packing instruction S: -
		Maximum quantity: -	Packing instruction S: -
		-	

14.7. Bulk transport according to annex II of MARPOL 73/78 and the IBC code.

Information non applicable.

SECTION 15. Regulatory information

Composition (648/04/EC): less than 5%: nonionic tensioactives, EDTA.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category. None.

Restrictions to the product or the substances contained therein according to Annex XVII Regulation (EC) 1907/2006.

Product.

Point. 3

Contained substances.

Point. 55 2-(2-BUTOXYETHOXY)ETHANOL Nr. Reg.: 01-2119475104-44

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorization (Annex XIV REACH).

None.

Substances subject to export notification Reg. (EC) 649/2012:

None.

Substances subject to the Rotterdam Convention:



CLEAN EXPRESS LIQUIDO

None.

Substances subject to the Stockholm Convention:

None.

Health controls.

Workers exposed to this hazardous chemical agent must have their health monitored in accordance with the provisions of art. 41 of Italian Law (D.Lgs.) 81 of 9 April 2008 unless the worker's health and safety risk is deemed to be irrelevant, according to the provisions of art. 224 par. 2.

D.Lgs. 152/2006 and amendments.

Emissions:

WATER 80.11 %

15.2. Chemical safety assessment

No chemical safety assessment was drawn up for the mixture or the substances contained therein.

SECTION 16. Other information

Hazard statements (H) referred to in sections 2-3 of the sheet:

Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritant, category 2
STOT SE 3	Specific toxicity for target organs - single exposure, category 3
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

KEY:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Half maximal effective concentration in the tested population
- EC NUMBER: Identification number in ESIS (European Chemical Substances Information System)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals
- IATA DGR: Dangerous Goods Regulations of the International Air Transport Association
- IC50: Half maximal inhibitory concentration in the tested population
- IMDG: International Maritime Dangerous Goods Code
- IMO: International Maritime Organization



CLEAN EXPRESS LIQUIDO

- INDEX NUMBER: Identification number in Annex VI of the CLP
- LC50: Lethal concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational exposure level
- PBT: Persistent Bioaccumulative and Toxic according to REACH
- PEC: Predicted environmental concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- TLV: Threshold Limit Value
- TLV CEILING: Absolute exposure limit that should not be exceeded at any time.
- TWA STEL: Spot exposure limit
- TWA: Time weighted average exposure
- VOC: Volatile organic compound
- vPvB: Very Persistent and very Bio-accumulative according to REACH
- WGK: Water hazard class (Germany).

GENERAL REFERENCES:

1. Regulation (EU) 1907/2006 of the European Parliament (REACH)
 2. Regulation (EU) 1272/2008 of the European Parliament (CLP)
 3. Regulation (EU) 790/2009 of the European Parliament (I Atp.) CLP
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 of the European Parliament (II Atp.) CLP
 6. Regulation (EU) 618/2012 of the European Parliament (III Atp.) CLP
 7. Regulation (EU) 487/2013 of the European Parliament (IV Atp.) CLP
 8. Regulation (EU) 944/2013 of the European Parliament (V Atp.) CLP
 9. Regulation (EU) 605/2014 of the European Parliament (VI Atp.) CLP
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA Agency website

User notes:

The information contained in this sheet is based on the knowledge available to the producer on the date of the last version. It is the user's responsibility to satisfy himself that the information is complete and suitable for his own particular use.

The document must not be interpreted as a guarantee of any specific properties of the product.

As the use of the product is not under the direct control of the producer, the user is responsible for ensuring compliance with all hygiene and safety laws and provisions in force. No liability shall be accepted for improper use.

Train staff appropriately in the use of chemical products.

Amendments compared to the previous version.

Modifications have been made to the following sections:

01 / 02 / 03 / 04 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.



Nuova Ricambi srl

Version no. 2

Revision date 27/07/2015

CLEAN EXPRESS LIQUIDO

Printed on 27/07/2015

Page no. 15/16

APPENDIX: EXPOSURE SCENARIOS- N.1

PHASE: TRANSFER OF THE PROFESSIONAL PRODUCT INTO CONTAINER (BUCKET/MACHINE)


(ref AISE GEIS.8a .1.a.v1)-

Open transfer of a concentrated product (with or without diluting); the cleaner is directly exposed to the product.



OPERATING CONDITIONS

Maximum duration	50 minutes/day
Process conditions	Process performed at room temperature Dilute if required with tap water at a maximum temperature of 45 °C. Local exhaust ventilation (LEV) is not required; generally efficient ventilation in the work place is sufficient

RISK MANAGEMENT MEASURES

Conditions and measures concerning personal protective equipment (PPE), health and hygiene evaluation	Use Gloves and protective goggles. See sect. 8 for specifications. Staff must be trained appropriately in use and maintenance 
-------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

GENERAL ADVICE

Do not eat, drink, smoke or use live flames	
Wash hands after use. Avoid contact with damaged skin Do not mix with other products	
Leakage instructions	Dilute with water and collect.
Additional advice	Follow the instructions on the label, the technical sheet and the SDS in sect. 7.

ENVIRONMENTAL MEASURES: Prevent the non-diluted product from reaching surface water.

PRODUCT COMPOSITION PROPERTIES

The classification of the concentrated product can be found on the label and in sect. 2 of the SDS
The product classification is based on the ingredient classification. The list of ingredients contributing to the product classification can be found in sect. 3 of the SDS.
The exposure evaluation is based on the key limit values of the ingredients indicated in sect. 8 of the SDS
The product may contain sensitizing components which may cause an allergic reaction in some people. Sect. 15 of the SDS lists these sensitizing components, where applicable to the product.

USE DESCRIPTORS

SU 22: Professional uses
PC 35: Washing and cleaning products (including solvent-based products)
PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
ERC 8a: Wide dispersive indoor use of processing aids in open systems



Nuova Ricambi srl

Version no. 2

Revision date 27/07/2015

CLEAN EXPRESS LIQUIDO

Printed on 27/07/2015

Page no. 16/16

APPENDIX: EXPOSURE SCENARIOS-N.4 C

PHASE: USING A PROFESSIONAL PRODUCT IN A SEMI CLOSED SYSTEM (ref AISE GEIS 2.1.a.V1)

Using a product in a machine where the cleaner could be exposed to the product/vapors (e.g. Tunnel washing)



OPERATING CONDITIONS

Maximum duration	480 minutes/day
Process conditions	Process performed at room temperature Local exhaust ventilation (LEV) is not required; generally efficient ventilation in the work place is sufficient

RISK MANAGEMENT MEASURES

Conditions and measures concerning personal protective equipment (PPE), health and hygiene evaluation	Personal protective equipment is not required.
-------------------------------------------------------------------------------------------------------	------------------------------------------------

GENERAL ADVICE

Do not eat, drink, smoke or use live flames	
Wash hands after use. Avoid contact with damaged skin Do not mix with other products	
Leakage instructions	Dilute with water and collect
Additional advice	Follow the instructions on the label, the technical sheet and the SDS in sect. 7.

ENVIRONMENTAL MEASURES: Prevent the non-diluted product from reaching surface water

PRODUCT COMPOSITION PROPERTIES

The classification of the concentrated product can be found on the label and in sect. 2 of the SDS
The product classification is based on the ingredient classification. The list of ingredients contributing to the product classification can be found in sect. 3 of the SDS.
The exposure evaluation is based on the key limit values of the ingredients indicated in sect. 8 of the SDS
The product may contain sensitizing components which may cause an allergic reaction in some people. Sect. 15 of the SDS lists these sensitizing components, where applicable to the product.

USE DESCRIPTORS

SU 22: Professional uses
PC 35: Washing and cleaning products (including solvent-based products)
PROC 2: Use in closed, continuous process with occasional controlled exposure
ERC 8a: Wide dispersive indoor use of processing aids in open systems